

TS5000(LiFePO<sub>4</sub> 51.2V100Ah, 5120.0Wh)



- Safety in use
- Low self discharge rate
- Good high temperature performance High
- Cycle times and long service life
- High energy density and conversion efficiency Environmental
- Friendly, without any heavy metals Easy installation, easy BMS
- modbus protocol can communicate with the inverter



Item		Specification
Electrical Characteristics	Nominal Voltage	51.2V
	Nominal Capacity	100Ah
	Energy	5120Wh
	Internal Resistance	≤20mΩ
	Cycle Life	6000 Cycles
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.2C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	57V ±0.2V
	Charge Mode	0.2C to 57V, then 57V, charge current 0.02C(CC/CV)
	Charger Current	100A
	Max. Charge Current	110A Protection
	Charge Cut-off Voltage	57V±0.2V
Standard Discharge	Continuous Current	100A
	Max. Pulse Current	115A
	Discharge Cut-off Voltage	42.6V
Environmental	Charge Temperature	0°C to 45°C (32F to 113F) @60±25% Relative Humidity
	Discharge Temperature	-20°C to 60°C (-4F to 140F) @60± 25% Relative Humidity
	Storage Temperature	0°C to 40°C (32F to 104F) @60± 25% Relative Humidity
	Water Dust Resistance	IP30
Mechanical	Cell & Method	3.2V 16S1P 100AH PRISMATIC
	Plastic Case	4U standard case
	Dimensions (in./mm.)	482*400*177MM
	Weight (lbs./kg.)	43Kg
	Terminal	100A through terminal
	Protocol (optional)	RS485/RS232CAN
	BMS	16S100A

Authorization Letter

We hereby certify that GREEN ENERGY ZA is authorized for supplying&process TAICO branded lifepo4 batteries in South Africa.

Validity period is Oct 30, 2023 to Oct 30, 2024

Issuer: SHENZHEN TAICO TECHNOLOGY CO., LTD  
 Authorized Distributor: GREEN ENERGY ZA  
 Product ranges: Lifepo4 Battery  
 Date: Friday, Oct 30, 2023

